

**Computer Vision Recognition of Metallic Objects Against A  
Poorly Contrasting Background**

BACKGROUND OF THE INVENTION

5    1. Field of the Invention

          The present invention relates to visualization of parts having metallic objects against a dielectric or non-metallic poorly contrasting background. The invention is particularly, but not exclusively, useful for recognizing  
10 by computer vision a Ball Grid Array (BGA) of small solder balls carried by a light colored ceramic substrate for the purposes of inspection and surface mounting the BGA on a circuit board or card.

15    2. Description of the Related Art

          Typical Ball Grid Arrays (BGAs) are described in IBM Application Note, "Ceramic Ball Grid Array Surface Mount Assembly and Rework", July 2000, obtainable at:

[http://www-3.ibm.com/chips/techlib/techlib.nsf/techdocs/  
20    852569B20050FF7785256996005B1D23/\\$file/bgaguide.pdf](http://www-3.ibm.com/chips/techlib/techlib.nsf/techdocs/852569B20050FF7785256996005B1D23/$file/bgaguide.pdf)

          In such publication, at page 10, it is indicated that in the case of BGA packages employing a white ceramic substrate, poor lighting contrast between the solder balls  
25 and the white ceramic substrate may make it difficult to tune a vision system, causing failure to properly recognize BGA packages and erroneous rejections.

          A BGA or Ceramic Ball Grid Array (CBGA) is a commonly used component or package in Surface Mount Technology  
30 (SMT). The bottom of the part is formed by high melt small (e.g. a fraction of a mm in diameter) solder balls arranged

in a predetermined, typically rectangular grid array,  
pattern on a ceramic substrate to which they are joined by  
eutectic solder fillets. The part is placed on a circuit  
board or card that has a matching pattern of contact pads  
5 on which eutectic solder paste has been applied. The  
circuit board or card is then run through an oven such that  
the solder paste forms fillets joining the solder balls to  
the contact pads.

Currently, a pick and place machine is used to pick  
10 the BGA, along with other parts, out of a storage location,  
and computer vision equipment, including an upwardly  
looking camera and frontal lighting, is employed by the  
pick and place machine to inspect the BGA, and if the BGA  
is not rejected, to steer the placement of the BGA on the  
15 circuit board or card with proper registration of the BGA  
balls to the circuit pads of the board or card. The BGA  
should be rejected if it has one or more missing balls,  
incorrect ball spacing, or nonsymmetrical ball size.

Most BGAs have a dark colored ceramic bottom and  
20 silver colored metallic balls. This combination provides  
excellent contrast between balls and background. Some BGAs  
have silver or gold colored metallic balls on a white or  
very light colored ceramic background. These parts do not  
provide sufficient visual contrast for current computer  
25 vision systems to reliably recognize the BGA.  
Specifically, when recognition using current camera and  
lighting is done on BGAs having a white or light colored  
bottom, the vision system cannot distinguish between balls  
and background because the balls appear almost as bright as  
30 the ceramic background.

One known technique used to attempt to improve the visualization and, as a result the recognition, of white ceramic BGAs, involves illuminating the part being visualized by so-called "coaxial lighting" wherein the illuminating light is introduced via a beam splitter in front of the camera lens so that the resulting illumination is coaxial with the lens of the camera. The use of such coaxial lighting has proven to be marginally effective at best. When coaxial lighting is used in combination with a rather expensive telecentric camera lens, a higher, but still substandard, level of successful recognition is achieved.

#### OBJECTS AND SUMMARY OF THE INVENTION

It is an object of the present invention to overcome the aforementioned deficiencies in the prior art visualization of metallic objects against a poorly contrasting dielectric background, and in particular to improve the visualization, and thus the rate of successful recognition, of white or light colored ceramic BGAs.

This and other objects of the present invention are satisfied by a method and apparatus in which the part being visualized is illuminated by linearly polarized electromagnetic radiation, e.g light passed through a polarization filter, and an image is formed of the electromagnetic radiation reflected from the part and passed through a polarization filter oriented to pass radiation having a polarization direction that is substantially orthogonal to the direction of polarization of the radiation illuminating the part. Because the radiation is reflected from the metallic objects or solder

balls with the same polarization direction as the illuminating radiation, substantially no radiation reflected from the metallic objects passes through the latter polarization filter and appears in the formed image.

- 5 On the other hand, because radiation reflected from the non-metallic or dielectric background is smeared in polarization and includes radiation with a polarization direction that is orthogonal to the polarization direction of the illuminating radiation, some radiation reflected
- 10 from the background passes through the latter polarization filter and appears in the formed image. Consequently, the part is visualized in the formed image with a substantial contrast between metallic objects and background, e.g. the metallic objects appear black, whereas the background
- 15 appears white or light colored, allowing for reliable computer vision recognition of the metallic objects.

- A method in accordance with the invention for visualization of a part having metallic objects against a light colored non-metallic background comprises
- 20 illuminating the part with electromagnetic radiation that is linearly polarized in a predetermined first direction, and forming an image of electromagnetic radiation reflected from the part viewed through a linear polarization filter oriented for passing electromagnetic radiation that is
- 25 linearly polarized in a second direction that is substantially orthogonal to the first polarization direction. Such method further comprises recognizing the metallic object in the formed image.

- Similarly, an apparatus in accordance with the present
- 30 invention for visualization of a part having metallic objects against a light colored non-metallic background

comprises one or more sources for illuminating the part with electromagnetic radiation that is linearly polarized, at least one of the sources producing electromagnetic radiation that is linearly polarized in a predetermined first direction, and an image forming device for forming an image of electromagnetic radiation reflected from the part viewed through a linear polarization filter oriented for passing electromagnetic radiation that is linearly polarized in a second direction that is substantially orthogonal to the first direction. Such apparatus further comprises a computer vision system for recognizing the metallic objects in the formed image, and still further comprises a manipulator for positioning the part on a circuit board or card with recognized metallic objects of the part in registration with contact pads of the board or card.

The invention also comprises a circuit board or card on which is surface mounted a part that has been recognized in accordance with the aforementioned method, such surface mounting being with recognized metallic objects of the part in registration with contact pads of the board or card.

Other objects, features and advantages of the present invention will become apparent upon perusal of the following detailed description when taken in conjunction with the appended drawing, wherein:

#### BRIEF DESCRIPTION OF THE DRAWING

Figure 1 is a schematic elevational cross-section view of visualization, recognition and placement apparatus in accordance with the invention, and

Figure 2 is a top view of illumination and reption parts of Figure 1, as viewed from the lines 2-2.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

5 Referring to Figures 1 and 2 of the drawing, the present invention for visualization of parts having metallic objects against a dielectric or non-metallic poorly contrasting background, is explained in conjunction with a conventional computer vision system 10 recognizing a  
10 usually two dimensional Ball Grid Array (BGA) 12 of small high melt solder balls 14 carried by a ceramic dielectric substrate 16. BGA 12 is held by a gripper or manipulator 18 of a pick and place machine (not shown) over an upwardly looking camera 20 of computer vision system 10. The camera  
15 20 forms and provides an electronic image to computer vision system 10, which system utilizes the electronic image to recognize and inspect the solder balls 14 of the BGA 12, as to existence, size and spacing. If the BGA 12 passes inspection, the vision system 10 steers the  
20 translation and placement of BGA 12 by manipulator 18 on a circuit board or card 22, with the recognized solder balls 14 of the BGA in registration with contact pads 24 of the board or card 22. As is conventional, prior to placement of the BGA 12 and other surface mount components on the  
25 circuit board or card 22 the contact pads 24 are coated with a eutectic solder paste, and after the placement of the BGA 12 and other surface mount components on circuit board or card 22, heat is applied to card with placed BGA and other components to fuse the solder paste into fillets  
30 (not shown) firmly surface mounting the BGA to the circuit board or card.

In the poorest contrast situation when the solder balls 14 are silver colored and the substrate 16 is white or light colored, the light box 26 is used to provide generally upwardly and inwardly directed polarized illumination I of BGA 12, in conjunction with a polarization filter 28 in front of the lens 30 of camera 20, in order to allow for proper visualization by camera 20, and proper recognition by vision system 10 of solder balls 14. A preferred embodiment of light box 26 has a central aperture 32 through which camera 20 looks upward via polarization filter 28, and four upwardly and outwardly inclined trapezoidal faces 34, 36, 38, 40 of a frusto-pyramid, each face forming a separate source of polarized light. The faces 34, 36, 38, and 40 comprise polarization filters 40, 42, 44, and 46 over respective milk glass diffuser panels 50, over LED arrays 52. With the direction of linear polarization passed by polarization filter 28 taken as  $0^\circ$ , polarization filters 40 and 44 are oriented to pass linear polarization directed at  $90^\circ$  and polarization filters 42 and 46 are oriented to pass linear polarization directed at  $180^\circ$ . The result is that the downwardly directed component of light from the four sources reflected from the solder balls 14 has a polarization at  $90^\circ$ , which is, or is nearly, orthogonal with the polarization direction that would be passed by polarization filter 28. Therefore no light reflected by solder balls 14 reach the lens 30 of camera 20. On the other hand, the downwardly directed component of light reflected from the white or light colored substrate 16 is substantially uniformly distributed in polarization and a substantial amount of light reflected downward from the substrate 16 passes

through polarization filter 28 and reaches the lens 30 of camera 20. As a result, in the electronic image formed by camera 20, the solder balls 14 appear substantially black and the substrate 16 appears substantially white, providing  
5 good contrast for reliable recognition of solder balls 14. This contrast producing effect is thought to be due to a preservation of polarization in reflection of electromagnetic radiation from shiny metal objects versus a the smearing of polarization in reflection of  
10 electromagnetic radiation from dielectric objects.

It should now be appreciated that the objects of the present invention have been satisfied. While the present invention has been described in particular detail, it should also be appreciated that numerous modifications are  
15 possible within the intended spirit and scope of the invention. In interpreting the appended claims it should be understood that:

- a) the word "comprising" does not exclude the presence of other elements or steps than those listed in a claim;
- 20 b) the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements.
- c) any reference signs in the claims do not limit their scope; and
- d) several "means" may be represented by the same item  
25 of hardware or software implemented structure or function.